



PIPE SIZE	ROD SIZE	MAX. DES. LOAD Kg	'A'	'B'
1"	1/2"	430	65	50
1 1/2"	5/8"	700	105	50
2"	5/8"	700	130	50
3"	5/8"	700	152	50
4"	3/4"	1140	165	50
6"	7/8"	1300	217	50
8"	7/8"	1300	243	75
10"	7/8"	1470	270	75
12"	7/8"	1470	295	75
14"	1"	1950	322	75
16"	1"	1950	348	75
18"	1"	1950	373	75
20"	1 1/4"	2500	403	75
24"	1 1/4"	2500	454	75

ROD LENGTH 'C' = 'D' - ('A' + 'B')

BILL OF MATERIALS

MARK No.	DESCRIPTION	No REQ'D PER UNIT
1	WELDED BEAM ATTACHMENT, ITT GRINNELL FIG. 66 OR EQUAL.	1
2	WELDED EYE ROD C/W TWO HEX HEAD NUTS, ITT GRINNELL FIG. 278 OR EQUAL.	1
3	PIPE CLAMP, ITT GRINNELL 295 OR EQUAL.	1

NOTES:

1. MAXIMUM ALLOWABLE TEMPERATURE 340°C
2. WHERE PIPE MATERIAL IS OTHER THAN CARBON STEEL, PIPE IS TO BE WRAPPED WITH PROTECTIVE TAPE BEFORE INSTALLATION OF PIPE CLAMP.

0	ISSUED FOR CONSTRUCTION						
REV	REVISION	DATE	DRN	CHK	ENG	APP	
CLIENT	TITLE PIPE SUPPORT STANDARD NPS 1" TO NPS 24" HANGER ROD FOR INSULATED LINES HR2						
PREPARED BY	SCALE N.T.S.	DWG. No. PSS-HR02	CLIENT DWG. No.	PROJ.	REV. 0		