



NOTES

1. ALL MATERIAL IS CARBON STEEL CSA G40.21 GR.350W OR GR.300W.
2. WHERE A SHOE IS USED IN COMBINATION WITH A REINFORCING PAD THE TOTAL SHOE HEIGHT MUST BE MAINTAINED BY TRIMMING THE SHOE BY THE AMOUNT OF THE REPAD THICKNESS.

|             |                         |  |                      |       |     |           |         |  |
|-------------|-------------------------|--|----------------------|-------|-----|-----------|---------|--|
|             |                         |  |                      |       |     |           |         |  |
| 0           | ISSUED FOR CONSTRUCTION |  |                      |       |     |           |         |  |
| REV         | REVISION                |  |                      | DATE  | DRN | CHK       | ENG APP |  |
| CLIENT      |                         | TITLE<br>PIPE SUPPORT STANDARD<br>PIPE SHOES 100 mm HIGH NPS 8" & BELOW<br>PS1 |                      |       |     |           |         |  |
| PREPARED BY |                         | SCALE<br>N.T.S.  | DWG. No.<br>PSS-PS01 | PROJ. |     | REV.<br>0 |         |  |
|             |                         | CLIENT<br>DWG. No.   |                      |       |     |           | 0       |  |