



**NOTES:**

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. WEEP HOLES TO BE GREASE SEALED (NOT WELDED).
3. WELD PIPE TO LOWER HALF OF RE-PAD BEFORE WELDING RE-PAD TO PIPE.
4. FIELD TRIM AS REQUIRED.

MK.	QTY	DESCRIPTION	MATERIAL
1	1	10" PIPE, XS	ASTM A333 GR. 6, SMLS
2	2	PL 25 x 180° WRAP, 600 LG., ID to match pipe	ASTM A516 grade 70
3	2	BAR 12 x 25 x 600 LG	CSA G40.21 GR. 350W
4	1	PL 25 x 180 x 370 LG	CSA G40.21 GR. 350W

0	ISSUED FOR CONSTRUCTION						
REV	REVISION	DATE	DRN	CHK	ENG	APP	

CLIENT		TITLE SPECIAL SUPPORT STANDARD VERTICAL GUIDE/ANCHOR FOR CSA PIPING SPS3					
PREPARED BY		SCALE	DWG. No.	SPS-0003	PROJ.	REV.	0
		N.T.S.	CLIENT DWG. No.				

SCALE APPLIES IF PLOTTED ON SIZE A (8.5"x11")